

CA290

290ml

Why use CA290

- Not just fast but INSTANT GRAB
- Save Time
- Avoid using fixings, clamps, screws or props
- Can use on almost any surface

Colour: Grey

Application

- Stone
- Concrete
- Ceramic
- Timber
- Glass/mirror
- Most Plastics
- Plasterboard
- Bricks
- Cement Fibre
- MDF
- Aluminium
- Metals

CA290 can be used in indoor/outdoor situations, be painted and retains elasticity. Perfect for structural bonding in vibrating conditions. Not suitable for PE, PET, PP, PC, PMMA, PTFE, neoprene, bituminous substrates and continual water immersion. Always test before use. For further information request our data sheet or scan the QR code.

Surface Preparations & Finishing

Application temperature +5°C to +40 °C (environment and substrate). Surfaces must be clean and dry. Always test adhesion prior to application. Apply with heavy duty applicator. Apply in vertical/horizontal strips to the size of the V nozzle.

Health & Safety

Product health and safety data sheet must be read and understood before use. These are available on request.

Warranty & Guarantee


Classic Architectural Group warrants that its product complies, within its shelf life, to its specification.



Made under the ISO 9001 quality system.


T 1300 244 377
E info@classic-arch.com
Melbourne • Sydney • Brisbane
Adelaide • Perth • Auckland

www.classic-arch.com



Scan to view instructions for use or more information.


For Best Performance



Use V-Shaped Nozzle (supplied) to allow a good uniform flow.




Use Caulking Gun with at least a 18:1 ratio.




Apply in straight lines with the V-shaped groove facing up, for triangular beads.

Vertical Application




For vertical applications, apply beads vertically.

Angle of Application



For triangular beads, keep the gun at an angle of 90° during application.

Steps



18 Months Warranty

CA290

Instant Grab Adhesive

Section 1. Company & Product Identification

Supplier: Classic Architectural Group
Address: 6 Beaufort St. Preston VIC 3072 Australia
Phone: 1300 244 377
Email: info@classic-arch.com
Product: CA290 – Instant grab adhesive
Product Code: CA290
Product Type: Sealant/Adhesive
Product Description: CA290 is a high-quality instant grip polymer adhesive designed for the building and construction industry. The product is odourless and silicone, solvent, phthalate, PVC and isocyanates free. After application the CA290 cures with atmospheric moisture.

Section 2. Hazard Identification

Hazard description: N/A
Information in relation to dangers for humans and the environment: This product doesn't have to be labelled due to the procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.
Classification process: This classification is according to the latest editions of the EU-lists and extended by company and literature data.

Section 3 - Composition/Information on Ingredients

Chemical characterization
Description: Mixtures of substances are listed below with non-hazardous additions.

Dangerous components:	CAS NO.	Approx WT%	Risk-phrase	Einecs
Trimethoxyvinylsilane	2768-02-7	1-<5%	Xn; R10-20	220-449-8

Additional information: For the wording of the listed risk phrases refer to section 16.

Section 4. First Aid Measures

After swallowing: If symptoms persist consult a doctor.
After inhalation: Move patient into fresh air. If breathing becomes difficult seek medical attention immediately.
After eye contact: Immediately flush with water, seek medical advice if necessary.
After skin contact: Wipe with paper towel and immediately clean with water and soap. Generally product does not irritate skin.
General information: No special measures required.

Section 5 - Fire Fighting Measures

Suitable extinguishing media: Use fire extinguishing methods suitable to surrounding conditions.
Protective equipment: Mouth respiratory protective device.

Section 6 - accidental release measures

Personal safety precautions: Ensure adequate ventilation
Environmental protection: Do not allow product to enter sewers/ surface or ground water.
Measures for cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Additional information: See section 8 for personal protection equipment.

Section 7 - Handling and Storage

Handling precautions: No special measures required.
Fire/Explosion: Precautions: No special measures required.
Storage precautions: No special measures required

Section 8 - Exposure Controls/Personal Protection

Workplace exposure: Not Applicable.
Personal protection hygienic measures: Usual precautionary measures are to be adhered to when handling chemicals. Always wash hands before eating, drinking and when leaving the workplace.
Respiratory protection: None required if used in well-ventilated area.
Hand protection: Always wear protective gloves. The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests, no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.
Penetration time of glove material: The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
Eye protection: Always wear protective or safety glasses during refilling.

Additional information about design of technical facilities: No further data; see item 7.

Ingredients with limit values that require monitoring at the workplace: The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

Additional information: The lists valid during the making were used as basis.

Section 9 - Physical and Chemical Properties

General Information:
Form: Pasty
Colour: Various
Odour: Characteristic
Change in condition:
Melting Point/ Range: Undetermined.
Boiling Point/ Range: Undetermined.
Flash point: >100°C
Ignition temperature: Undetermined.
Self-igniting: Product is not self-igniting.
Danger of explosion: Product does not present an explosion hazard.
Vapour pressure: Undetermined.
Density at 20°C: 1.56 g/cm³
Solubility in / miscibility with water: Not miscible or difficult to mix.
pH-value: Undetermined.
Solvent content VOC (EC): 2.23% - 35.3 g/l

Section 10 - Chemical Stability and Reactivity Information

Thermal decomposition/Conditions to be avoided: No decomposition if used according to specifications.
Dangerous reactions: No dangerous reactions known.
Dangerous decomposition products: No dangerous decomposition products known.

Section 11 - Toxicological Information

Acute toxicity
Skin: No irritant effect.
Eye: No irritant effect.
Sensitization: No sensitising effects known.
Additional information: The product is not subject to classification according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version. When used and handled according to specifications, the product does not have any harmful effects to our experience and the information provided to us.

Section 12 - Ecological Information

General notes: Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewerage systems.

Section 13 - Disposal Considerations

Product recommendation: Disposal must be made according to official regulations.
European waste catalogue: 08 04 09 waste adhesives and sealants containing organic solvents or other dangerous substances.
Uncleaned packaging recommendation: Disposal must be made according to official regulations.

Section 14 - Transportation Information

Land transport ADR/ RID: (cross-border) ADR/RID class: NA
Maritime transport IMDG: IMDG Class: NA
Air transport ICAO-TI & IATA-DGR: ICAO/IATA Class: NA

Section 15 - Regulatory Information

Labelling according to EU guidelines: Observe the general safety regulations when handling chemicals. The product is not subject to identification regulations under EU Directives and the Ordinance on Hazardous Materials (German GefStoV).
Directive 2012/18/EU
Named dangerous substances – Annex I – None of the ingredients listed
REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 40
Special labelling of certain preparations: Contains N-(3-(trimethoxysilyl)propyl) ethylenediamine, N-[3-(dimethoxymethylsilyl)propyl] ethylenediamine. May produce an allergic reaction.
Note: Safety data sheet available for professional user on request.

Section 16 - Other Information

Additional information: The information in this MSDS is based on our present knowledge to the date of this publication. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship. It is only a guide for safe handling, use, storage, transporting and disposal of the product.
Relevant phrases:
H226: Flammable Liquid & Vapour
H332: Harmful if inhaled