



classic
architectural group

For Every Step



Product Data Sheet

Studio

Ribbed Carpet Tile Matting

Crush resistant carpet tile matting

Integra Studio has been specifically developed with a unique ribbed pattern which provides a highly effective scraping action. Its special construction and the density of its polypropylene pile forms an effective moisture-absorbing barrier, competently arresting the spread of moisture, dirt and grit to maintain the life and safety of your floors.

Specification Guide

Install Integra Studio carpet style entrance matting comprising of dual-fibre large crush-resistant polypropylene fibres. If required, install Integra INFR08 aluminium mat frame to suit recess, in accordance with manufacturer's recommendations. Available from Classic Architectural Group, 1300 244 377, info@classic-arch.com

Application

Recess into mat wells, wall-to-wall in airlocks and lobbies.

Suitable for: Commercial office buildings, shopping centres, hotels, motels, airports, schools and universities, hospitals and aged care homes, all public domains - libraries, etc.



Suitable for medium to high traffic applications



Easy to clean



Good dirt removal & hiding ability



Suitable for wheelchairs and other wheeled traffic



Low profile loop-pile design



Releases trapped particles when vacuumed



Easy to transport and install



Modular system



Heel-proof design



Lifetime warranty.
Customer satisfaction
guarantee.



Installation Services
available



Carbon

Colour Guide

This guide shows the available matting insert colour mentioned in the specifications for this product. Please note that these swatches are to remain as a guide only and actual colours may vary.

Benefits

- Achieve unlimited size and design combinations including patterns and borders
- Modular tile system allows easy on-site mat installation, and shaping without the need for specialised equipment
- Easy removal of trapped dirt and particles when cleaning
- Enhances interior appearance and acoustics
- Reduces floor maintenance and cleaning costs
- Heel-proof to D.D.A. standards for peace of mind regarding OH&S
- Easy replacement of worn tiles
- Compatible with electronic tagging systems



Technical Specifications

Nominal Size

Modular tile 500mm x 500mm

Construction ISO 2424

Fusion bonded needlefelt

Pile Yarn Composition ISO 2424

100% PP

Pile Weight

950 g/m² nom

Pile Height ISO 1765

4.5mm average

Total thickness ISO 1765

8.5mm average

Total mass ISO 8543

3890 g /m² nom

Backing

Non woven polymer matrix, with fibre-reinforced BT backing

Carton Quantity

5.0 m² (20 tiles per carton)

Colors

Carbon

Frames

Suits the INFR08 framing system

Installation options

Linear, Quarter turn, Random lay



Performance Specification

Classification EN 1307

Heavy duty

Flammability

EN 13501-1

Efl'

Dimensional stability EN 669, EN 1307

Yes, pass

Stair suitability EN 1307

No

Edge integrity EN 1307

Fray resistant

Electrostatic Resistance EN 14041

Yes



Environmental Assessment

L.I.F.E. Program

Product takeback program.

This product's manufacture is environmentally compatible, and includes the use of recycled materials and production waste, and the use of recycled raw materials.



Lifetime warranty.
Customer satisfaction
guarantee.



Installation Services
available