



**classic**  
architectural group

**For Every Step**

## Product Data Sheet

# Zone

## Dirt & Moisture Barrier Carpet Matting

Polyamide cut pile carpet style matting

Integra Zone architectural entrance matting has been proven in many highly demanding environments, as both a primary and as a secondary level of matting. The attractive, cut pile provides a luxurious look and feel, while the dual weave non-static polyamide fibre composition efficiently removes and absorbs water and grit. Zone is incorporated into the Integra Vantt 5500 & 7500 series and Link matting ranges allowing designer colour coordination and the cohesive flow of various matting zones.

## Specification Guide

Install Integra Zone carpet style entrance matting in colour (insert colour), comprising of 100% polyamide non-static tufted pile with Intraback vinyl backing. If required, install Integra INFR08 aluminium mat frame to suit recess, or bevelled rubber edging for loose lay applications, in accordance with manufacturer's recommendations. Available from Classic Architectural Group, 1300 244 377, [info@classic-arch.com](mailto:info@classic-arch.com)

## Application

Can be installed as loose lay mats with bevelled edging, recessed into mat wells, or wall-to-wall in lobbies and atriums.

**Suitable for:** High traffic, and high-end corporate entrances, hospitals, schools, universities, shopping centres, retail stores, stadiums, etc.



Suitable for high traffic applications



Easy to clean



Resistant to fungal and bacterial growth



Suitable for wheelchairs and other wheeled traffic



High fire resistant rating



Easy to transport and install



Lifetime warranty.  
Customer satisfaction  
guarantee.



**Installation Services**  
available



Midnight



Storm



Slate



Haze



Solar



Twilight



Cobalt



Sulphur



Clay



Lava

## Colour Guide

This guide shows the available colours mentioned in the specifications for each product. Please note that these swatches are to remain as a guide only and actual colours may vary.

### Benefits

- Enhances interior appearance and acoustics
- Reduces floor maintenance and cleaning costs
- Minimises costly slip-and-fall accidents
- High water absorption
- Vinyl backing and edging helps reduce creeping
- Certified as meeting stringent international green ratings for environmentally friendly manufacture, recyclability, and low VOC levels

### Environmental Assessment

**VOC Emission** ISO 16000-6, EN 10580

TVOC after 4 weeks  $\leq 100 \text{ ug/m}^3$

### Green Certification

PRODIS-GUT Certificate E18BB887

This fulfills the GUT requirements (compliance with thresholds and ban of use regarding VOC emissions, harmful substances and odor)

### L.I.F.E. Program

Product takeback program.

This product's manufacture is environmentally compatible, and includes the use of recycled materials and production waste, and the use of recycled raw materials.



### Technical Specifications

#### Nominal Size

2000mm wide roll (incl edging)  
cut to length

#### Construction

ISO 2424  
Tufted cutpile

#### Pile Yarn composition

ISO 2424  
100% PA6

#### Pile weight

900 g/m<sup>2</sup> nom

#### Pile Height

ISO 1765  
5.8mm average

#### Total thickness

ISO 1765  
9.0mm average.

#### Total mass

ISO 8543  
3460 g /m<sup>2</sup> nom

#### Backing

Non woven polymer matrix,  
with Intraback vinyl backing

#### Roll Quantity

50 m<sup>2</sup> (25 l/m per roll)

#### Colors

Midnight, Storm, Slate, Smoke, Solar,  
Twilight, Cobalt, Sulphur, Clay, Lava

#### Frames

Suits the INFR08 framing system

#### Installation options

Linear



### Performance Specification

#### Classification

EN 1307  
Commercial

#### Flammability

Radiant Panel test EN ISO 9293-1

- CRF = 11.2 kW/m<sup>2</sup>

- Smoke = 258 %.minutes

#### Caster Chair Stability

EN 985  
Yes, incidental use

#### Stair Stability

EN 1307  
Yes

#### Colorfastness

- to light ISO 105-B02  $\geq 5$

- to rubbing ISO 105-X12  $\geq 4$   
(wet & dry)

- to water ISO 105-E01  $\geq 4$

- to soiling EN 1269  $\geq 3,5$

#### Electrostatic Resistance

EN 14041  
Yes



Lifetime warranty.  
Customer satisfaction  
guarantee.



Installation Services  
available