



SPECIFICATION GUIDE

Classic Tredfx

Fastile PT30A

Polyurethane TGSI Warning 300 x 300 Tactile Tile

Product: Classic Tredfx Fastile PT30A Polyurethane TGSI Warning 300 x 300 Tactile Tile

Finish: Polyurethane

Colour Options: Black, Blue, Red, Tangerine, Mid Grey, Yellow, Beige, Light Grey, White & Magenta

Dimensions: 300mm W x 300mm L

Fixing Method: Self-adhesive Fixing, suitable for stone, masonry, tile and timber (to be installed in accordance with the manufacturer's instructions)

Warranty: Product lifetime

CHF: Critical Radiant Flux is 7.8 kW/m²

Smoke: Smoke Development Rate is 234%/min

LRV: Black - Dry 2.4, Wet 2.6, White - Dry 61.3, Wet 62.1, Blue- Dry 4.3, Wet 4.7, Red - Dry 8.5, Wet 9.2, Tangerine - Dry 25.4, Wet 25.7, Mid Grey - Dry 12.9, Wet 14.2, Yellow - Dry 49.0, Wet 48.8, Beige - Dry 33.5, Wet 34.7, Light Grey - Dry 47.8, Wet 47.7

Slip Rating: P5

Compliance: Complies with current AS 1428 standards

Supplier: Classic Architectural Group. Phone: 1300 244 377 Fax: 1300 768 876 Email: info@classic-arch.com Website: <https://classic-arch.com/>