



SPECIFICATION GUIDE

Classic Tredfx

SBR104-H

Solid Brass Safety Stair Nosing for Surface Mount Applications

Product: Classic Tredfx SBR104-H Solid Brass Stair Nosing with Polymer Insert for Surface Mount Applications

Profile Colour: Solid Brass

Insert Colour Options: Black, Blue, Dark Grey, Red, Tangerine, Mid Grey, Yellow, Beige, Light Grey, White, Ultra Violet,

Raspberry, Teal, Lime Green, Coral

Dimensions: Length 3650mm

Application: Surface Mount, suited to concrete, timber, tile, masonry & metal substrates. To be installed in accordance

with the manufacturer's instructions.

Warranty: Product lifetime

CHF: Critical Radiant Flux is 7.8 kW/m2

Smoke: Smoke Development Rate is 234 %/min.

Slip: P3

LRV Ratings:

Colour	Dry	Wet
Black	4.1	3,5
Blue	8.7	7.5
Dark Grey	6.5	6.1
Red	17,8	16.6
Tangerine	24.6	23,5
Mid Grey	24.4	23,9
Yellow	57,0	56.7
Beige	51.6	50.1
Light Grey	45.4	44.7
White	74.9	74.2
Ultra Violet	20.1	19.6
Raspberry	22.1	22,0
Teal	23,6	23.1
Lime Green	35.4	35.3
Coral	34.0	34,0

Compliance: Complies with current AS 1428 standards

Supplier: Classic Architectural Group. Phone: 1300 244 377 Fax: 1300 768 876 Email: info@classic-arch.com Website: https://classic-arch.com/