



Classic Integra

Studio Matting Tiles

Ribbed Carpet Tile Matting


Classic Integra Studio Matting Tile has been specifically developed with a unique ribbed pattern which provides a highly effective scraping action. A highly effective moisture absorbing barrier is created by the polypropylene pile. The thick pile helping to absorb moisture, and the special construction enhancing the mats ability to capture grit and dirt.

Application

Recess into mat wells, wall-to-wall in airlocks and lobbies.


Suitable for: Commercial office buildings, shopping centres, hotels, motels, airports, schools and universities, hospitals and aged care homes, all public domains - libraries, etc.


 Suitable for medium to high traffic applications


 Easy to clean

 Good dirt removal and hiding ability

 Suitable for wheelchairs and other wheeled traffic

 Low profile tufted design

 Releases trapped particles when vacuumed


 Easy to transport and install

 Modular system

 Heel-proof design

 LRV (Light Reflectance Value) available

 P5 Slip resistance rating

 Fire test report available

**LIFETIME
WARRANTY**

**INSTALLATION
SERVICES
AVAILABLE**

**NCC
COMPLIANT**

**AS1428
COMPLIANT**



Matting Colours



Carbon

Features

- Achieve unlimited size combinations of colour and design including patterns and borders
- Modular tile system allows easy on-site mat installation, and shaping without the need for specialised equipment
- Easy removal of trapped dirt and particles when cleaning
- Enhances interior appearance and acoustics
- Reduces floor maintenance and cleaning costs
- Heel-proof to D.D.A. standards for peace of mind regarding OH&S
- Easy replacement of worn tiles
- Compatible with electronic tagging systems

Environmental Assessment

L.I.F.E. Program

Product takeback program.

This product's manufacture is environmentally compatible, and includes the use of recycled materials and production waste, and the use of recycled raw materials.



Specification Guide

Nominal Size

Modular tile 500mm x 500mm

Construction

ISO 2424 Tufted cutpile

Pile Yarn Composition

ISO 2424 Fusion bonded needle felt

Pile Yarn Composition ISO 2424

100% PP

Pile Weight

950 g/m2 nom

Pile Height ISO 1765

4.5mm average

Total thickness ISO 1765

8.5mm average

Total mass ISO 8543

3890 g /m2 nom

Backing

Non woven polymer matrix, with fibre-reinforced BT backing

Carton Quantity

5.0 m2 (20 tiles per carton)

Frames

Suits the INFR08 framing system

Installation options

Linear, Quarter turn, Random lay



Performance Guide

Classification EN 1307

Heavy duty

Flammability

EN 13501-1
Efl'

Dimensional stability EN 669, EN 1307

Yes, pass

Stair suitability EN 1307

No

Edge integrity EN 1307

Fray resistant

Electrostatic Resistance EN 14041

Yes