



SPECIFICATION GUIDE

Classic Integra **Vantt 5500** Roll-up Aluminium Matting

Product: Classic Integra Vantt 5500 Aluminium Matting

Material: Aluminium Frame with Matting Inserts

Frame Finish Options: Natural, Black, Bronze, Saffron, Gold

Insert Colour Options: Midnight, Storm, Ribbed Polymer, Grit, Slate, Clay, Lava, Cobalt, Sulphur, Coco, Haze

Dimensions: Thickness - 10.0mm average

Fixing Method: Recessed (suits the INFR11 framing system) or Surface Mount (Suits the INFR1180 ramp framing system). To be installed in accordance with the manufacturer's instructions.

Warranty: Product lifetime

CHF: Matting Insert - Critical Radiant Flux is 10.2 kW/m², Grit Insert - Critical Radiant Flux is ≥11 kW/m²

Smoke: Matting Insert - Smoke Development Rate is 23 %/min, Grit Insert - Smoke Development Rate is 8 %/min

Slip: P5

Compliance: Complies with current AS 1428 standards

Certifications: Global GreenTag™ GreenRate™ Level A (does not include Grit & Ribbed Polymer inserts)

Supplier: Classic Architectural Group. Phone: 1300 244 377 Fax: 1300 768 876 Email: info@classic-arch.com Website: <https://classic-arch.com/>