



classic
architectural group

For Every Step



Classic Integra

Vantt 9500

Roll-up Aluminium Matting

Classic Integra Vantt 9500 features a wider slat, giving it a more carpet like appearance. Like the Vantt 5500, it has an innovative flexible interlocking system that allows for easy customisation to fit any shape, with individually replaceable slats to ensure long-lasting performance. The matting inserts are made from our premium Zone product, a non-static polyamide pile matting that delivers exceptional cleaning results. Unlike competitors, our inserts are constructed as a complete piece per strip, providing greater durability and ensuring the mat retains its sleek, premium look for years, without gaps or movement.


The aluminium frame is made from low-emission materials, and the Zone inserts are GUT-certified, meeting our strict sustainability standards. The efficient framing system ensures straightforward installation, while local manufacturing and supply contribute to shorter lead times, typically under two weeks.

Application

Classic Integra Vantt 9500 requires a depth of 14mm, therefore can be either surface mounted or recessed into airlocks and lobbies. The product can be cut into any shape or form providing the solution for architecturally shaped entrances and revolving doorways.

Suitable for

Commercial office buildings, residential apartments, sporting facilities, shopping centres, hotels, airports, schools and universities, hospital and aged care homes, all public domains – libraries, etc.



Suitable for high traffic applications

Easy to clean, highly effective scrape and wipe cleaning action

Wheelchair friendly

Rubber cushioned back for quietness underfoot

Rolls up easily for cleaning

Easily shaped for curved entrances or revolving doors

Easy interlocking system

Carpet insert is GUT certified

P5 Slip resistance rating

Fire test report available

**LIFETIME
WARRANTY**

**INSTALLATION
SERVICES
AVAILABLE**

**NCC
COMPLIANT**

**AS1428
COMPLIANT**



Matting Colours



Storm



Slate



Midnight



Clay



Lava



Haze

Aluminium Colours

Upon request



Black



Natural



Bronze



Saffron



Gold

Features

- Colour range co-ordinates with the Integra Zone range of matting and enables a cohesive colour flow
- Reduces cleaning time of surrounding floor finishes
- Minimises costly slip-and-fall accidents
- Stops dirt at the door for a cleaner environment
- Enhances entrance appearance and acoustics

Specification Guide

Nominal Size

Made to order

Custom Shaping

Yes can be shaped to any size and shape

Construction

ISO 2424 Tufted cutpile

Pile Yarn Composition

ISO 2424 10 0% PA6

Pile Weight

900 g/m² nom

Pile Height

ISO 1765 5.8mm average

Total Thickness

ISO 1765 10.0mm average

Total Mass

ISO 8543 8000 g/m² nom

Backing

Non woven polymer matrix, with Intraback vinyl backing

Frames

Suits the INFR11 framing system

Performance Guide

Classification

EN 1307 Commercial

Flammability

Radiant Panel test ASISO 9239.1-2003
Certificate No. 7-586702-AV
- CRF = 8.1 kW/m²
- Smoke = 192 %.minutes

Colorfastness

-to light	ISO 105-B02	≥5
-to rubbing	ISO 105-X12	≥4
	(wet & dry)	
-to water	ISO 105-E01	≥4
-to soiling	EN 1269	≥3,5

Electrostatic Resistance

EN 14041Yes