



classic
architectural group

For Every Step



Classic Integra

Zone

Dirt and Moisture Barrier Carpet Matting

Classic Integra Zone architectural entrance matting has been proven in many highly demanding environments, as both a primary and as a secondary level of matting. The attractive, cut pile provides a luxurious look and feel, while the dual weave non-static polyamide fibre composition efficiently removes and absorbs water and grit. Integra Zone is incorporated into the Integra Vantt and Link matting ranges, allowing designer colour coordination and the cohesive flow of various matting zones.

Application

Can be installed as loose lay mats with bevelled edging, recessed into mat wells, or wall-to-wall in lobbies and atriums.

Suitable for: High traffic, and high-end corporate entrances, hospitals, schools, universities, shopping centres, retail stores, stadiums, etc.

 Suitable for high traffic applications

 Easy to clean

 Resistant to fungal and bacterial growth

 Suitable for wheelchairs and other wheeled traffic

 Easy to transport and install

 LRV (Light Reflectance Value) available

 P5 Slip resistance rating

 Fire test report available

**LIFETIME
WARRANTY**

**INSTALLATION
SERVICES
AVAILABLE**

**NCC
COMPLIANT**

**AS1428
COMPLIANT**



Matting Colours



Midnight



Storm



Clay



Cobalt



Slate



Lava



Sulphur



Shale



Haze



Coco

Features

- Enhances interior appearance and acoustics
- Reduces floor maintenance and cleaning costs
- Minimises costly slip-and-fall accidents
- High water absorption
- Vinyl backing and edging helps reduce creeping
- Certified as meeting stringent international green ratings for environmentally friendly manufacture, recyclability and low VOC levels

Environmental Assessment

VOC Emission

ISO 16000-6, EN 10580
TVOC after 4 weeks \square 100 ug/m³

Green Certification

PRODIS-GUT Certificate E18BB887
This fulfills the GUT requirements (compliance with thresholds and ban of use regarding VOC emissions, harmful substances and odor)

L.I.F.E. Program

Product takeback program. This product's manufacture is environmentally compatible, and includes the use of recycled materials and production waste, and the use of recycled raw materials.



Specification Guide

Nominal Size

2000mm wide roll (incl edging)
cut to length

Construction

ISO 2424 Tufted cutpile

Pile Yarn Composition

ISO 2424 100% PA6

Pile Weight

900 g/m² nom

Pile Height

ISO 1765 5.8mm average

Total Thickness

ISO 1765 9.0mm average.

Total Mass

ISO 8543 3460 g /m² nom

Backing

Non woven polymer matrix,
with Intraback vinyl backing

Frames

Suits the INFR08 framing system

Installation options

Linear

Performance Guide

Classification

EN 1307 Commercial

Flammability

Radiant Panel test EN ISO 9293-1
- CRF = 11.2 kW/m²
- Smoke = 258 %.minutes

Caster Chair Stability EN 985

Yes, incidental use

Stair Stability EN 1307

Yes

Colorfastness

-to light	ISO 105-B02	≥ 5
-to rubbing	ISO 105-X12	≥ 4
	(wet & dry)	
-to water	ISO 105-E01	≥ 4
-to soiling	EN 1269	$\geq 3,5$

Electrostatic Resistance

EN 14041
Yes